


TERCOR NB LIQUID

Corrosion Inhibitor



Description

Tercor NB Liquid is a compound liquid of nitrite and borate with organic corrosion inhibitors for scale and corrosion control in closed re-circulation water-cooling systems.

Chemical & Physical Properties

- **Appearance:** Clear/Hazy Thin Liquid
- **Specific Gravity:** 1.3
- **Flammability :** Non Flammable
- **Solubility in Water:** Soluble
- **pH:** 12.5 Approx.

Application & Method Of Use

Application:

- ⊕ An effective corrosion inhibitor for diesel engine cooling water systems, closed loops centralised cooling circuits and hot water heating system.
- ⊕ Suitable for use with fresh or distilled.
- ⊕ Safe and effective with usual ferrous and non-ferrous metals found in cooling water systems.
- ⊕ Nitrite-Borate is approved by numerous diesel engine manufacturers and the UK Department of Trade where potable water is produced from fresh water generators which are integral with the engine cooling system.

Method of Use:

- Initial dose for untreated system 10 litres/1000 liters of cooling water.
- On-going dose depends on the maintenance of a nitrite level of 1200 to 1800ppm nitrite (NO₂) using the TERCO nitrite test kit. We recommend 1500ppm nitrite as a convenient mid-point.
- Water quality should not exceed 50ppm chloride and 100ppm hardness as CaCO₃. The pH should be maintained between 8.3 and 10.0.
- Inject chemical to the expansion tank or via a pot feeder if fitted.
- If the system is heavily contaminated with oil we recommend cleaning by the addition of up to 5% by volume of Degreasol Tank Cleaner or Cold Wash circulating preferably hot for 4-6 hours draining and flushing.

TERCOR NB LIQUID

Corrosion Inhibitor

Dilution Ratio

- See Application & Method of Use above.

Precautions

Refer to Hazard Identification as per Safety Data Sheet.

Safety, Transport & Storage Information

Please refer to Safety Data Sheet.

Packaging

Available in 20L & 200L containers. Containers non-returnable.

IMPORTANT: FOR DETAILED INFORMATION ABOUT THIS PRODUCT PLEASE REFER TO SAFETY DATA SHEET.

The product information contained in this document is to the best of our knowledge and non-binding. Our statements relating to possible uses of the product do not constitute a guarantee that such uses are appropriate in a particular user's case or that such uses do not infringe the patents or proprietary rights of any third party. We assume no risk or liability whatever in connection with any particular use, if not expressly confirmed by us in writing. Therefore Chemetall grants no warranty and does not accept any liability in connection with this product information or its use. Except where noted otherwise, all registered trademarks are owned by Chemetall or its affiliated companies. The reproduction of any or all of the information contained in this document is expressly forbidden without Chemetall's prior written consent.